

## TECHNICAL DATA SHEET

### Cat6a FTP (10Gb/s)

PATCHSEE RJ45 Patch Cords are designed, and individual tested for connecting the network equipment to patch panel and network user outlet. They are guaranteed for cat 6A TIA/EIA-568-B-2.10 Channel test on a Permanent Link certified for transmission frequencies of up to 500 MHz and compatible with the 10 Gigabits applications. And Standard compliance with ISO/IEC 11801 ed 2002-Amd1 & Amd2.

#### PATCHSEE Solution and main characteristics

- Light identification by plastic optical fiber,
- PCI (Patchsee Connector Insert : PatchSee Property)
  - o designed to improve NEXT and RL for 10 Gigabits applications,
  - o designed for high density panels and active components (same size as the plug in width and height)
- 25 years Guarantee
- certified for 10 Gb/s applications
- Individually tested: each Patch Cord is individual tested (Return Loss, Attenuation, NEXT, etc...)
- Various lengths from 2 feet (0.6 m) up to 16 feet (4.9 m)
- Color of sheath: Black with white marking
- Color of boot: Black with white marking
- Removable color clip, 16 colors available
- Available in crossover
- Marking on the boot: length and P/N
- Unique serial number marking on the cable



<b>Number of pairs</b>	4
<b>Type</b>	U-FTP (STP)
<b>Conductor</b>	Stranded bare copper wire, 7/0.16 +/- 0.005 mm
<b>Gage</b>	26 AWG
<b>Insulation</b>	Foam Skin Polyethylene
<b>Individual pair screen</b>	Al-laminated metal pair foil
<b>Pair Screen</b>	n a
<b>Optical wave guide</b>	2 POF 0.5 mm
<b>Drain</b>	Stranded drain wire tinned copper, 26 AWG
<b>Jacket</b>	LSOH Black with white printing (LSOH : IIEC 60332-3 Cat C, Low Smoke : IIEC 61189-2C12, Halogen Free : IPC4101-A)
<b>Overall diameter</b>	5.9 +/- 0.2 mm
<b>Plug housing</b>	UL 1863 Polycarbonate , individual wire guide and management bar
<b>Contacts</b>	Moved contacts
<b>Contact Plating</b>	50 µ inches gold minimum (1.2 µm)
<b>Shielding</b>	Tin-plated

#### Mechanical Properties of the cable

Fire Propagation Test	Temperature range During	Fire load	Bending radius
UL 1581 VW 1 Flame test	-20°C up to +75°C	372 MJ/km	>25 mm without load

#### Electrical Properties of the cable (at 20°C +/- 5°C)

Conductor resistance	Insulation resistance	Mutual Capacitance	Impedance 1-100MHz	Impedance 100-250MHz	Propagation delay	Test voltage
< 1400/km	> 150 M0/km	56nF/km	100 +/- 15 0	100 +/- 15 0	< 45 ns/100m	2 500 V -3 seconds



**HELEC Sales & Systems**

9 Pullens Rd., WOODBRIDGE, Tasmania 7162  
Phone: 03 6267 4897

[www.helec.com.au](http://www.helec.com.au) [sales@helec.com.au](mailto:sales@helec.com.au)